

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**


**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: <b>A61F 2/02</b>	<b>AI</b>	(11) International Publication Number: <b>WO 97/43982</b> (43) International Publication Date: 27 November 1997 (27.11.97)
(21) International Application Number: PCT/US97/08787 (22) International Filing Date: 21 May 1997 (21.05.97) (30) Priority Data: 08/652,887                      23 May 1996 (23.05.96)                      US (71)(72) Applicants and Inventors: KRESCH, Arnold, J. [US/US]; Suite 206, 780 Welch Road, Palo Alto, CA 94304 (US). KOVAC, Tim, J. [US/US]; 33 Ashlar Avenue, Los Gatos, CA 95030 (US). (74) Agents: RAFFLE, John, T. et al.; Townsend and Townsend and Crew LLP, 8th floor, Two Embarcadero Center, San Francisco, CA 94111-3834 (US).		(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published With international search report.

(54) Title: DEVICE AND METHOD FOR TREATING FEMALE INCONTINENCE



## (57) Abstract

A female urinary incontinence device (2) and method comprises an elongate body (4) and a pair of anterior support members (6, 8) extending from the proximal end of the elongate body. The anterior support members are spaced from each other and configured for elevating and/or supporting the superior vaginal tissue (122) on each side of the bladder neck (106) to normalize urodynamic parameters without completely occluding the urethra (108) so that the patient may urinate or not urinate, if desired. A pair of posterior support members (10, 12) extend from the distal end of the elongate body for engaging the posterior vaginal wall (120) to provide longitudinal support to the anterior support members. The device may be folded axially between a collapsed position for insertion into the vagina (100) and an expanded position for supporting the bladder neck to offer counterpressure to intrabladder pressure so that continence is preserved.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NR	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	R	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## DEVICE AND METHOD FOR TREATING FEMALE INCONTINENCE

## BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to incontinence and more particularly to a non-surgical device and method for controlling female urinary incontinence.

Urinary incontinence in women has long been a serious problem that requires medical attention. Stress incontinence, the involuntary loss of urine during exertional activities, is the typical cause of incontinence and is most prevalent among women aged 35-65 and those who have had multiple vaginal deliveries. This condition may be caused either by a weakness of the intrinsic urethral sphincter muscle or by the abnormal descent of the urethra and bladder neck below the pelvic floor muscle with increased intra-abdominal pressure. During coughing, sneezing, laughing, physical exercise or the like (i.e., when strain is placed upon the bladder), the patient involuntarily releases a small volume of urine from the urethra. This involuntary urine release is unpleasant, embarrassing and may contaminate the genital sections of the woman.

The descent of the bladder neck that contributes to female incontinence may often be repaired with surgical procedures. Surgical repair of female incontinence generally involves securing the paraurethral tissues to the periosteum of the pubic bone or the rectus facia to elevate the bladder neck above the pelvic floor muscle and thereby distribute pressure equally to the bladder, bladder neck and pelvic urethra. This operation may be performed through an incision in the vaginal wall or the abdomen. While this surgery has often proved successful, it can be traumatic to the patient and, in elderly or infirm patients, the risk of surgery may be too great to justify the surgical procedure. In addition, while the surgical techniques are often effective for periods

of several years, the urethra may break loose following extensive activity, thereby causing a reoccurrence of the urinary incontinence condition.

5 The problems associated with surgical procedures have resulted in the development of a number of non-surgical incontinence devices. These devices are generally inserted into the vagina or directly into the urethra by the surgeon or the patient. Incontinence devices inserted into the urethra typically include an occluding member for blocking flow of  
10 urine through the bladder neck during sudden tensioning of the abdominal muscles. Incontinence devices inserted into the vagina are typically expanded, e.g., by inflating an expandable member such as a balloon, in an upward direction against the anterior wall of the vagina to apply pressure  
15 against the bladder neck. This pressure inhibits or completely prevents the flow of urine through the urethra.

Existing non-surgical urinary incontinence devices suffer from a number of drawbacks. For example, many of these devices tend to block all or substantially all flow of urine  
20 from the bladder. Therefore, when a patient needs to urinate, the device must be removed from the vagina or urethra or the device must be collapsed to remove the pressure applied against the bladder neck (e.g., by deflating a balloon). In an attempt to solve or at least mitigate this problem,  
25 incontinence devices have been developed that support the upper urethra without completely blocking the bladder neck so that the patient may urinate with the device in place. These devices, however, are generally large and intrusive and, therefore, are uncomfortable to wear, and they may irritate  
30 the tender mucosal tissue within the vagina after a period of time (particularly when the patient is active, e.g., during physical exercise). In addition, these devices are relatively expensive to manufacture and, therefore, they are either designed for re-use and/or they must remain within the  
35 patient's vagina for a relatively long period of time (i.e., 24 hours or longer).

For these and other reasons, it would be desirable to provide methods and devices for controlling urinary

incontinence in women. These methods and devices should be capable of elevating the bladder neck and/or supporting the vaginal tissue on each side of the urethra to offer counterpressure to intra-abdominal pressure and thereby preserve continence. Furthermore, this female incontinence device should be minimally intrusive to maximize comfort and minimize irritation of the tender mucosal tissues within the vagina. Additionally, the female incontinence device should be relatively inexpensive to manufacture and easy to remove and insert so that it can be used for shorter time periods, such as during physical activity, if desired.

## 2. Description of the Background Art

U.S. Patent No. 4,920,986 to Biswas describes an inter-vaginal device for controlling urinary incontinence that includes a body member with a forward portion for engaging the anterior vaginal wall adjacent the bladder neck to lift the neck and base of the bladder above the pelvic floor muscle thereby maintaining continence. U.S. Patent Nos. 5,386,836 and 5,007,894 describe female incontinence devices that incorporate inflatable body members that may be inserted into the vagina and inflated into a position for maintaining continence. The body members include two opposed projections that form a cradle for receiving and supporting the neck of the bladder. U.S. Patent No. 5,417,226 to Juma describes an incontinence device that may be inserted directly into the urethra and incorporates a flexible disk for occluding the bladder neck during sudden tensioning of the abdominal muscles.

## SUMMARY OF THE INVENTION

The present invention provides a non-surgical device and method for controlling female urinary incontinence. The device comprises an elongate body with proximal and distal ends and one or more anterior support members extending from the proximal end of the elongate body. When the device includes more than one anterior support member, they are movable between a collapsed or longitudinal position, where

the device is configured for insertion into the patient's vagina, and an expanded position, where the anterior support members are spaced apart from each other for supporting and/or elevating the bladder neck to minimize incontinence. The  
5 elongate body and anterior support members have a relatively narrow, non-intrusive profile that generally conforms to the patient's vagina, thereby increasing comfort and minimizing irritation of the tender mucosal tissues within the vagina. In addition, the anterior support members are configured to  
10 normalize the patient's urodynamic parameters without completely occluding the urethra so that the patient may urinate, if desired.

In a specific configuration, the anterior support members are first and second arms extending laterally and  
15 longitudinally from the proximal end of the elongate body and first and second hemispherical bladder support members contiguous with the first and second arms, respectively. The hemispherical bladder support members have a curved, atraumatic surface for engaging the vaginal tissue around the  
20 bladder neck, thereby minimizing irritation of this tissue. The arms extend away from the elongate body so that, when the device is suitably positioned within the patient's vagina, the hemispherical support members elevate and support the bladder neck above the pelvic floor muscle. The anterior support  
25 members and the elongate body are preferably moved into the collapsed position by folding them together along the longitudinal axis of the body. In this manner, the device can be quickly and easily folded and then introduced into the vagina by the surgeon or the patient. The anterior support  
30 members are preferably biased towards the expanded position (e.g., by the elastic properties of the support members) so that they will automatically expand away from each other once the surgeon or patient releases them within the patient's vagina.

35 The incontinent device of the present invention further includes one or more posterior support members extending from the distal end of the elongate body for engaging the posterior vaginal wall. The posterior support

member(s) brace the elongate body between the posterior vaginal wall and the urethra to provide longitudinal support to the anterior support members. In a specific configuration, a pair of posterior support members are spaced apart from each other in the expanded configuration such that they contact the posterior vaginal wall on either side of the colon and/or rectum. Preferably, the posterior support members are first and second arcuate paddles extending laterally and longitudinally from the distal portion of the elongate body to provide a laterally displaced load against the patient's pelvic structure. In this manner, the posterior support members provide sufficient longitudinal support to the anterior support members to keep these members in position against the bladder neck, while minimizing interference with the soft tissue at the colon and/or rectum.

In an exemplary embodiment, the device is manufactured from a disposable material, such as paper, paper fiber, cotton or a flexible, elastic and inexpensive material, such as plastic, elastomers, PET, polycarb, ABS, silicone rubber and the like, so that the patient can simply remove and dispose the device when desired. In this manner, a patient suffering from stress incontinence may insert the device for a specific, relatively short, time period, such as during physical activity, and then remove and dispose the device at the conclusion of that activity.

The incontinence device of the present invention may be inserted into the vagina manually or with an insertion device or introducer. In the latter configuration, the introducer preferably comprises a hollow shaft having an inner lumen sized to receive the incontinence device in the collapsed position. The shaft is inserted into the patient's vagina by the physician or the patient so that its distal end is suitably positioned adjacent the patient's bladder neck, and the incontinence device is propelled through the distal end of the hollow shaft with a pusher mechanism, such as a plunger or the like. The incontinence device expands upon release from the hollow shaft, and the anterior support members are engaged against the bladder neck. The physician



or patient then removes the shaft, allowing the posterior support member(s) of the device to move into position against the posterior vaginal wall.

Other features and advantages to the invention will appear from the following description in which the preferred embodiment has been set forth in detail in conjunction with the accompanying drawings.

10

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a female urinary incontinence device according to the present invention;

Fig. 2 is a top view of the incontinence device of Fig. 1;

15

Fig. 3 is a side view of the incontinence device of Fig. 1;

Figs. 4A and 4B are front views of the incontinence device of Fig. 1;

20

Fig. 5 is a transverse cross-sectional view of the female pelvic organs illustrating the female incontinence device of the present invention in place within the vagina;

Fig. 6 is a top cross-sectional view of the female incontinence device of Fig. 1 within the patient's vagina, illustrating anterior support members of the incontinence device elevating and supporting the bladder neck;

25

Fig. 7 is top view of the incontinence device of Fig. 1 in a collapsed, longitudinal position for insertion into the vagina;

30

Figs. 8A and 8B are side views of one of the anterior support members, illustrating an alternative embodiment in which the anterior support members can be folded to facilitate insertion into and removal from the patient's vagina; and

35

Figs. 9A and 9B schematically illustrate an introducer and a method for inserting the incontinence device of Fig. 1 into the vagina.

## DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Referring to the drawings in detail, wherein like numerals indicate like elements, a female urinary incontinence device 2 is illustrated according to the principles of the present invention. As shown in Fig. 1, incontinence device 2 generally comprises an elongate body 4 and first and second anterior support members 6, 8 for supporting and/or elevating the patient's bladder neck. Device 2 further includes first and second posterior support members 10, 12 for bracing the body 4 between the posterior vaginal wall and the urethra to provide longitudinal support to the anterior support members.

Referring to Figs. 1-4, elongate body 4 has a proximal end 14, a distal end 16 and a longitudinal axis 17 therebetween. As best shown in Figs. 4A and 4B, body 4 preferably has a generally U-shaped transverse cross-section to facilitate folding body 4 lengthwise along the longitudinal axis 17 into a collapsed, longitudinal position for insertion into the patient's vagina 100 (see Figs. 5 and 7). Of course, it will be recognized that body 4 may have cross-sectional shapes other than U-shaped, such as solid, tubular and the like. The dimensions of elongate body 4 (i.e., length, width and shape) generally conform to the dimensions of the vagina 100 so that incontinence device 2 is minimally intrusive to the patient. To that end, body 4 will usually have a width in the range of 0.05 to 0.7 inch and preferably in the range of 0.2 to 0.4 inch and a length in the range of 0.5 to 1.0 inch. In addition, body 4 defines an arcuate lower surface 18 for bearing against the posterior vaginal wall 120, as shown in Figs. 3 and 5. Lower surface 18 has a curvature substantially similar to the curvature of the posterior vaginal wall 120 so that elongate body 4 generally conforms to a portion of this wall. Alternatively, lower surface 18 may be substantially straight and body 4 constructed of a flexible material that will deform into a curvature that conforms to the posterior vaginal wall 120.

Anterior support members 6, 8 each comprise an arm 19, 20 contiguous with and extending from proximal end 14 of body 4 and a bladder support member 22, 24 attached to arms

19, 20, respectively. As best shown in Fig. 4A, bladder support members 22, 24 are preferably hemispherical and define an inner cavity 26 and a curved, atraumatic surface 28 for pressing upward against the tissue immediately lateral to the urethra 110 (Figs. 5 and 6). Bladder support members 22, 24 preferably comprise an elastic, atraumatic material, such as paper, cotton, polymers and the like, for engaging the soft anterior vaginal tissue 122 around the bladder neck. Bladder support members 22, 24 preferably have radius of curvature of about 0.1 to 0.3 and a width of about 0.2 to 0.3 inch. It should be understood that bladder support members 22, 24 may comprise a variety of other shapes and sizes so long as the support members provide the necessary support to the muscles surrounding the bladder neck 106 in a generally atraumatic manner that will minimize irritation and/or damage to the vaginal tissue.

As shown in Figs. 4A and 4B, bladder support members 22, 24 each include a tab 30 extending downward from a lower surface 32 of members 22, 24. Tabs 30 serve to protect the tender vaginal tissue from the edges between the lower and curved surfaces 32, 28 of bladder support members 22, 24. To facilitate the manufacture of tabs 30, each tab is configured for movement between a first, as manufactured, position (Fig. 4A), where tabs 30 extend substantially vertically downward from lower surface 32 of members 22, 24, and a second use position (Fig. 4B), where tabs 30 are folded upward so that the tip 34 of each tab 30 extends substantially parallel to the lower surface 32 of support members 22, 24. In this manner, tabs 30 may be manufactured, e.g., injection molded or thermoformed, in the vertical first position and then folded into the second, use position prior to insertion of device 2 into the vagina 100. Of course, it will be recognized by those in the art that a variety of other means may be used to smooth the edges of support members 22, 24, including folding a hemispherical tab (not shown) underneath the lower surface 32 of support members 22, 24.

Referring to Figs. 1, 2, 5 and 6, arms 19, 20 each extend laterally and longitudinally from proximal end 14 of

elongate body 4 to space bladder support members 22, 24 on either side of the bladder neck 106). In addition, arms 19, 20 extend transversely to the plane of elongate body 4 such that, when lower surface 18 bears against the posterior vaginal wall 120, bladder support members 22, 24 are suitably positioned to elevate and support the bladder neck 106 above the pelvic floor muscle (not illustrated). Preferably, arms 19, 20 each include a first portion 36 extending from proximal end 14 substantially parallel to body 4 and a second portion 38 contiguous with first portion 36 and extending laterally outward from body 4. First and second arm portions 36, 38 are slender, non-intrusive and relatively easy to manipulate so that the surgeon or patient can quickly and easily position bladder support members 22, 24 against the bladder neck 106. First portions 36 of arms 19, 20 define a cradle 40 therebetween for receiving and supporting the neck of the patient's bladder (see Fig. 6). First portions 36 will usually be spaced a distance of 0.2 to 0.5 inch and preferably 0.25 to 0.3 inch from each other. These dimensions, of course, will vary depending on the requirements of the individual patient.

Second portions 38 of arms 19, 20 extend laterally outward to space bladder support members 22, 24 a suitable distance apart for positioning on either side of the bladder neck. Bladder support members 22, 24 will usually be spaced apart a distance of 0.5 to 1.0 inch and preferably 0.6 to 0.8 inch. Bladder support members 22, 24 provide tension to the muscle on either side of the urethra 108, thereby allowing the muscle to counter bladder pressure and/or intra-abdominal pressure to preserve continence. Note that the anterior support member 6, 8 are preferably designed so that the bladder neck or urethra is partially occluded or occluded by tissue tension adequate to prevent involuntary and/or voluntary urination, but not completely blocked off so that the patient may urinate, if desired.

Referring to Fig. 1, posterior support members 10, 12 preferably comprise arcuate paddles 50, 52 contiguous with and extending laterally and longitudinally from distal end 16

of elongate body 4. As best shown in Fig. 2, paddles 50, 52 include a first portion 54 that extends transversely to the plane of elongate body 4 and a second portion 56 that extends substantially parallel to the plane of body 4. Second portions 56 of paddles 50, 52 each define outer load distributing surfaces 60 (Figs. 1 and 2) for bearing against the posterior vaginal wall 120 and the patient's pelvic structure, as discussed in detail below. Paddles 50, 52 each have an arcuate shape designed to act in a cupping manner when displaced perpendicularly to the plane formed by the paddles 50, 52. This cupping action allows paddles 50, 52 to bear laterally against the patient's pelvic structure.

Referring to Figs. 3 and 5, second portions 56 of paddles 50, 52 are spaced apart a distance sufficient to engage and bear against the posterior vaginal wall on either side of the patient's colon 104 and/or rectum (not shown). This configuration minimizes contact between the paddles 50, 52 and the patient's colon 104 or rectum so to minimize loading and possibly herniating the soft tissue of the colon 104. In addition, the spaced configuration of paddles 50, 52 effectively avoids any possible obstruction of the patient's bowel movements. For a typical patient, second portions 56 will be spaced a distance in the range of 0.5 to 2.0 inches and preferably 1.0 to 1.5 inches.

Referring to Fig. 5, incontinence device 2 is sized and configured to effectively elevate, support and/or occlude the bladder neck 106 of the patient. To this end, posterior support members 10, 12 are sized to brace elongate body 4 and anterior support members 6, 8 between the posterior vaginal wall 120 and the urethra 108 to provide longitudinal support to anterior support members 6, 8, thereby offering counterpressure to intra-abdominal pressure so that continence is preserved. Usually, device 2 will have an overall length of about 3.0 to 5.0 inches and preferably 3.5 to 4.0 inches. In addition, body 4 will preferably have a smaller length than posterior and anterior support members 6, 8, 10, 12. Specifically, posterior support members will usually have a length in the range of 1.0 to 3.0 inches and more preferably

1.5 to 2.5 inches and anterior support members (including arms 19, 20 and bladder support members 22, 24) will have a length in the range of 0.8 to 1.5 inches. The relative dimensions of the support members and body of device 2 allow anterior support members 6, 8 to form cradle 40 for receiving and supporting the bladder neck 106 and facilitate manipulation and placement of anterior support members 6, 8 against the bladder neck 106 (Fig. 6). In addition, posterior support members 8, 10 are substantially longer than body 4 so that a relatively long inner space is formed between the posterior support members 10, 12. This space effectively ensures that the support members will not interfere with the patient's colon 104.

Incontinence device 2 is movable between a collapsed or longitudinal position (Fig. 7), where the device is configured for insertion into the patient's vagina 100, and an expanded position (Fig. 5), where the device is configured to form a brace between the posterior vaginal wall 120 and the urethra 108 to minimize incontinence. In a preferred configuration, elongate body 4 is configured to fold axially about the longitudinal axis such that posterior and anterior support members 6, 8, 10, 12 move towards each other into a substantially longitudinal configuration (see Fig. 7). Preferably, incontinence device 2 will have a maximum lateral dimension of 0.3 to 1.0 inches in the longitudinal or collapsed position.

Incontinence device 2 comprises a flexible, biocompatible material, such as plastic, paper, cotton, polymers or the like, that may be folded into the longitudinal configuration and that has a sufficient degree of elasticity to automatically unfold into the expanded position after being inserted into the patient's vagina. In a preferred configuration, device 2 will be constructed of a material that is relatively inexpensive and easy to manufacture. In this manner, incontinence device 2 is disposable so that the patient can insert the device for a relatively short period of time, if desired (e.g., in preparation for physical exercise and the like). The disposable material may comprise a

variety of relatively inexpensive material such as cardboard, paper, plastic and the like.

In a specific configuration, incontinence device 2 will comprise a material that degrades after a period of time within the vagina or when the patient actuates a trigger mechanism, e.g., pulling on a string 128 (Figs. 8A and 8B) attached to device 2. In this manner, the incontinence device may be automatically disposed when, for example, the patient urinates. For this configuration, device will be constructed of a material that gradually loses its integrity, such as fiber binders that degrade in a moist environment.

Referring to Figs. 5-7, the method of the present invention for inserting and removing female incontinence device 2 will now be described. As shown in Fig. 7, device 2 is folded into the longitudinal configuration such that anterior and posterior support members 6, 8, 10, 12 are in contact or in close proximity with each other. Device 2 is then introduced into the vagina 100 until posterior support members 10, 12 reach the posterior fornix 102 of the uterus 103 (Fig. 5). The device may be inserted into the vagina 100 in the doctor's office or by the patient at home. The insertion is similar to that of a diaphragm or tampon. As device 2 approaches the proper location, device 2 is allowed to unfold within the vagina 100 so that posterior support members 10, 12 bear laterally outward against the pelvic structure on either side of the colon 104. The doctor or patient then locates anterior support members 6, 8 to ensure that they are on each side of the upper urethra 108 and that members 19, 20 press up against the bladder neck 106.

As shown in Fig. 6, anterior support members 6, 8 exert supporting pressure against the anterior vaginal wall 110, laterally and adjacent to each side of the urethra to allow tissue between the vaginal mucosa and the urethra 108 produce a lateral pressure upon the upper section of the urethra 108 or the bladder neck 106. This pressure provides a slight reduction in the cross-sectional area of the urethra 108 and provides the muscles of the bladder neck 106 with tension to resist pressure. In this manner, the muscles will

offer counterpressure when inter-abdominal and/or intra-bladder 112 pressure is suddenly raised as it is during coughing, sneezing, laughing and physical exercise. The inter-abdominal pressure is transmitted to the upper urethra so that the closure pressure remains positive regardless of the changes in the intra-abdominal pressure such that continence is preserved. Posterior support members 10, 12 bear laterally against the pelvic structure to brace anterior support members 6, 8 against the bladder neck 106, thereby effectively ensuring that the device remains in place as shown in Fig. 5.

After device 2 is inserted within the vagina 100, the patient may proceed with normal physical activities characteristic of everyday life. Since the device supplements the natural uretral muscle action of the patient, it is generally not necessary to remove device 2 when the patient desires to urinate. On the other hand, since the device is disposable and relatively inexpensive, the patient may remove device 2 after the physical activity has been completed. To accomplish this, the patient grasps one or both of the anterior support members 6, 8 or a proximal portion of body 4 and folds device 2 completely or partially along the longitudinal axis to decrease its profile. Device 2 is then removed from the vagina, where it can be suitably disposed.

Figs. 8A and 8B illustrate an alternative embodiment of an anterior support member 6', illustrating a method for folding support member 6 between an expanded, substantially elongate, configuration (Fig. 8A) for supporting the bladder neck and a collapsed configuration for insertion into and removal from the vagina (note that Fig. 8B only illustrates support member 6' in a partially collapsed configuration). As shown, arm 19' defines a slot 120 extending therethrough and a pair of notches 122, 124 one either side of slot 120. An elongate member, such as a string 126, is wrapped around arm 19' within notches 122, 124.

In use, the operator applies tension to string 126, which causes arm 19' to fold over slot 124 in the direction of the arrows in Fig. 8B. Folding arm 19' in this manner will



facilitate the insertion and removal of the incontinence device into the patient's vagina. String 126 preferably has a length sufficient to extend toward the opening of the patient's vagina when the incontinent device is in position with anterior support member 6' engaged to the bladder neck. In this manner, the patient will be able to pull on a free end 128 of string 126 when removing the device.

Figs. 9A and 9b schematically illustrate an alternative system and method of inserting incontinence device 2 into the patient's vagina employing an introducer 150 instead of manually inserting device 2 as described above. Referring to Fig. 9A, introducer 150 comprises a hollow, cylindrical tube 152 having open proximal and distal ends 154, 156 and an axial lumen 158 therebetween sized to receive device 2 in the collapsed position. A pusher element, such as a piston 160 or the like, is used to propel device 2 from lumen 158.

As shown in Fig. 9A, for example, incontinence device 2 is collapsed and positioned within lumen 158 so that posterior support members 10, 12 face distal end 156 of tube 152. Tube 152 is then inserted into the patient's vagina 100 so that distal end 156 is positioned proximal of the posterior fornix 102 of the uterus 103 (see Fig. 9B). The patient or physician then moves piston 160 through proximal end 154 of tube 152 against device 2. Preferably, tube 152 is then withdrawn from the vagina while piston 160 holds device 2 in place. Device 2 automatically unfolds after tube 152 is withdrawn so that posterior support members 10, 12 bear against the pelvic structure and anterior support members 6, 8 are positioned on either side of the urethra 108 (see Fig. 5). In an alternative method, distal end 156 of tube 152 is positioned at the proximal end of the vagina and piston 160 is forced through tube 152 to propel incontinence device 2 through distal end 156.

Although the foregoing invention has been described in detail for purposes of clarity of understanding, it will be obvious that certain modifications may be practiced within the scope of the appended claims. For example, although the

present invention has been described in terms of a disposable incontinence device, device 2 may comprise a more sturdy, biocompatible material, such as an elastomer, that remains continuously within the vagina for a period of one or more days or months. Alternatively, device may comprise a material that can be re-used. In this configuration, the patient may remove and cleanse the incontinence device when desired.

In addition, it should be clearly understood that the incontinence device of the present invention is not limited to a pair of anterior support members and a pair of posterior support members as described above and shown in the Figures. For example, device 2 may include a single posterior support member extending from end 16 of body 4. The posterior support member may simply be an extension of body, it may have a similar paddle shape as described above, or it may have a hemispherical shape, e.g., one that substantially conforms to the shape of the posterior vaginal wall. In addition, the device may comprise more than two anterior support members, if desired. Alternatively, the anterior support members may include a bridge or web portion that extends between the members to facilitate support of the bladder neck.

WHAT IS CLAIMED IS:

- 1           1.    A device for removable insertion into the  
2    vagina of a female patient for controlling incontinence, the  
3    device comprising:  
4            an elongate body having proximal and distal ends and  
5    a longitudinal axis therebetween; and  
6            first and second anterior support members extending  
7    from the proximal end of the body, the anterior support  
8    members being configured to spread-apart and engage and  
9    support the anterior vaginal tissue on each side of the  
10   bladder neck to minimize incontinence, the anterior support  
11   members further being collapsible about the longitudinal axis  
12   to close together for insertion into the vagina.
- 1           2.    The device of claim 1 wherein the anterior  
2    support members are foldable together along the longitudinal  
3    axis in the collapsed position.
- 1           3.    The device of claim 1 wherein the anterior  
2    support members comprise an elastic material that biases the  
3    anterior support members into the spread-apart position.
- 1           4.    The device of claim 1 wherein the elongate body  
2    comprises a flexible material that is axially foldable into  
3    the collapsed position.
- 1           5.    The device of claim 1 further comprising first  
2    and second posterior support members extending from the distal  
3    end of the body and configured to contact the posterior  
4    vaginal wall when the anterior support members are in contact  
5    with the anterior vaginal tissue on each side of the bladder  
6    neck.
- 1           6.    The device of claim 1 further comprising first  
2    and second posterior support members extending from the distal  
3    end of the body, the posterior support members being  
4    configured to engage the posterior vaginal wall on either side

5 of the rectum and bear against pelvic structures, the  
6 posterior support members further being collapsible about the  
7 longitudinal axis to close together for insertion into the  
8 vagina.

1 7. The device of claim 1 wherein the anterior  
2 support members each comprise an atraumatic surface for  
3 contacting the vaginal tissue.

1 8. The device of claim 1 wherein the anterior  
2 support members each comprise an arm extending laterally and  
3 longitudinally away from the proximal end of the elongate  
4 body, and a support member having a spherical radius and being  
5 contiguous with the arm remote from the elongate body.

1 9. The device of claim 5 wherein the posterior  
2 support member arms extend laterally and longitudinally away  
3 from the distal end of the elongate body, the posterior  
4 support member arms having an arcuate shape for providing a  
5 substantial surface area to bear against tissue.

1 10. The device of claim 1 wherein the device  
2 comprises a disposable material.

1 11. The device of claim 10 wherein the disposable  
2 material is selected from a group consisting of paper,  
3 plastic, cotton and elastomers.

1 12. The device of claim 5 wherein the anterior and  
2 posterior support members and the elongate body extend a  
3 distance in the longitudinal direction in the range of 3 to 4  
4 inches.

1 13. The device of claim 5 wherein the posterior  
2 support members are spaced by a distance in the range of 0.5  
3 to 1.5 inches.

1           14. The device of claim 1 wherein the anterior  
2 support members each comprise an arm extending from the  
3 proximal end of the elongate body, the arms being movable  
4 between elongate and collapsed configurations.

1           15. The device of claim 14 wherein the arms each  
2 define a slot, the device further comprising an elongate  
3 member wrapped around each arm over the slot and having a free  
4 end extending from the arm, wherein applying tension to the  
5 elongate member around the arm causes the arm to fold over the  
6 slot into the collapsed configuration.

1           16. A device for being removably inserted into the  
2 vagina of a female patient for controlling incontinence, the  
3 device comprising:

4           an elongate body having proximal and distal ends and  
5 a longitudinal axis therebetween;

6           one or more support structures extending from the  
7 proximal end of the body and configured to engage and support  
8 the anterior vaginal tissue on each side of the bladder neck;  
9 and

10          at least one posterior support member extending from  
11 the distal end of the body and configured to contact the  
12 posterior vaginal wall when the anterior support members are  
13 in contact with the anterior vaginal tissue on each side of  
14 the bladder neck.

1           17. The device of claim 16 comprising first and  
2 second posterior support members spaced from each other and  
3 sized to brace the elongate body between the posterior vaginal  
4 wall and the urethra to provide longitudinal support to the  
5 anterior support members, thereby offering tissue tension to  
6 resist involuntary flow of urine so that continence is  
7 preserved.

1           18. The device of claim 17 wherein the posterior  
2 support members each define a load distributing surface for

3 contacting the posterior vaginal wall on either side of the  
4 rectum and/or the pelvic structure.

1 19. The device of claim 17 wherein the elongate  
2 body and the posterior and anterior support members are  
3 movable between a collapsed position, where the device is  
4 configured for insertion into the vagina, and an expanded  
5 position, where the device is configured to form a brace  
6 between the posterior vaginal wall and the paraurethral tissue  
7 to minimize incontinence.

1 20. The device of claim 19 wherein the posterior  
2 and anterior support members are folded together along the  
3 longitudinal axis in the collapsed position.

1 21. A method for treating female incontinence  
2 comprising:  
3 collapsing first and second anterior support members  
4 into a substantially longitudinal configuration in close  
5 proximity with each other;  
6 inserting the anterior support members into the  
7 vagina of the patient;  
8 allowing the anterior support members to move into  
9 an expanded position spaced apart from each other; and  
10 positioning the first and second anterior support  
11 members on each side of the urethra to support the anterior  
12 vaginal tissue on either side of the bladder neck so that  
13 continence is preserved.

1 22. The method of claim 21 further comprising  
2 collapsing first and second posterior support members into a  
3 substantially longitudinal configuration in close proximity  
4 with each other and inserting the posterior support members  
5 into the vagina, wherein the posterior support members are  
6 attached to the anterior support members to brace the anterior  
7 support members against the bladder neck.

1           23. The method of claim 22 further comprising  
2 allowing the posterior support members to move apart from each  
3 other and positioning the posterior support members against  
4 the posterior vaginal wall on either side of the colon.

1           24. The method of claim 23 further comprising  
2 applying lateral pressure against the posterior vaginal wall  
3 with the posterior support members to brace the posterior and  
4 anterior support members and the elongate body member between  
5 the posterior vaginal wall and the urethra and provide  
6 longitudinal support to the anterior support members, thereby  
7 offering tissue tension to intra-bladder pressure so that  
8 continence is preserved.

1           25. The method of claim 22 wherein the anterior and  
2 posterior support members are folded towards each other into  
3 the longitudinal configuration.

1           26. The method of claim 25 further comprising  
2 axially folding the elongate body member into the longitudinal  
3 configuration.

1           27. The method of claim 22 further comprising  
2 biasing the anterior and posterior support members into the  
3 expanded position.

1           28. The method of claim 21 further comprising  
2 removing the elongate body and anterior support members from  
3 the vagina.

1           29. The method of claim 28 further comprising  
2 folding each anterior support member before the removing step.

1           30. The method of claim 28 wherein the folding step  
2 is carried out by pulling a free end of a string wrapped  
3 around each anterior support member.

1           31. A method for introducing an incontinence device  
2     into a patient's vagina comprising:  
3           locating the incontinence device at least partially  
4     within an axial lumen of a hollow shaft;  
5           inserting at least a distal portion of the shaft  
6     into the patient's vagina; and  
7           discharging the incontinence device into the  
8     patient's vagina such that one or more anterior support  
9     members of the device is positioned adjacent to the bladder  
10    neck.

1           32. The method of claim 31 wherein the locating  
2     step comprises:  
3           collapsing first and second anterior support members  
4     into a substantially longitudinal configuration in close  
5     proximity with each other; and  
6           inserting an elongate body and the anterior support  
7     members into the axial lumen of the shaft.

1           33. The method of claim 32 wherein the discharging  
2     step comprises positioning a piston adjacent the proximal end  
3     of the hollow shaft and axially moving the piston relative to  
4     the shaft to force the incontinence device through the distal  
5     end of the shaft.

1           34. The method of claim 33 wherein the axially  
2     moving step is carried out by holding the piston and  
3     withdrawing the shaft from the patient's vagina.

1           35. The method of claim 32 wherein the discharging  
2     step includes allowing the anterior support members to move  
3     into an expanded position spaced apart from each other, and  
4     positioning the first and second anterior support members on  
5     each side of the urethra to support the anterior vaginal  
6     tissue on either side of the bladder neck so that continence  
7     is preserved.



1           36. The method of claim 31 wherein the locating  
2 step comprises collapsing first and second posterior support  
3 members into a substantially longitudinal configuration in  
4 close proximity with each other and inserting the posterior  
5 support members into the vagina.

1           37. The method of claim 36 wherein the discharging  
2 step includes allowing the posterior support members to move  
3 apart from each other and positioning the posterior support  
4 members against the posterior vaginal wall on either side of  
5 the colon.

1           38. A system of controlling female urinary  
2 incontinence comprising:  
3           an introducer comprising a hollow shaft with  
4 proximal and distal ends and an axial lumen therebetween, the  
5 distal end being configured for insertion into a patient's  
6 vagina;  
7           a support device configured for positioning with the  
8 axial lumen of the introducer and having one or more support  
9 structures configured to engage and support the anterior  
10 vaginal tissue adjacent the bladder neck; and  
11           a drive for propelling the support device from the  
12 axial lumen through the distal end of the shaft and into the  
13 patient's vagina.

1           39. The system of claim 38 wherein the support  
2 structures are anterior support members configured to spread-  
3 apart and engage and support the anterior vaginal tissue on  
4 each side of the bladder neck to minimize incontinence and  
5 further being collapsible about the longitudinal axis to close  
6 together for insertion into the axial lumen of the introducer  
7 shaft.






FIG. 3




FIG. 4A




FIG. 4B




FIG. 5

4/7




FIG. 6







FIG. 7

5/7




6/7



F 16 9A

7/7

**FIG. 9B**



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US97/08787

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61F 2/02

US CL : 600/029

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 600/029-031

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US 5,036,867 A (BISWAS) 06 August, 1991, entire document.	1-7, 9-11, 16-20 ----- 8, 12-14
A	US 5,007,894 A (ENHORNING) 16 April 1991, Fig. 3.	15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	* T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A document defining the general state of the art which is not considered to be of particular relevance	* K	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* E earlier document published on or after the international filing date	* Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* G	document member of the same patent family
* O document referring to an oral disclosure, use, exhibition or other means		
* P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

19 JULY 1997

Date of mailing of the international search report

30 JUL 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ROSILAND S. KEARNEY

Telephone No. (703) 308-2711